

Technical Specifications

Specifications:	Standard	Optional
Processor:	National "Geode". Pentium II MMX	
Speed:	300 MHz	450 MHz (Q3)
Operating System:	Win CE 3.0 Win NT/2000-embedded or full	Linux
Memory:	128 MB SDRAM	512 MB
Expansion Slots:	PCI Slots (2) ISA Slots (1)	
Hard Drive:	60 GB Ultra DMA 33	Up to 240 GB
CD/DVD:		2 nd IDE drive bay for CD/DVD Expansion
Modem:	V.90 / 56k Compatible	
LAN:	10/100 Mbit/sec. Ethernet	
Power:	120/240VAC-40 Watts max.	
Certification:	FCC class "A" CE class "A" UL/CSA	International (per requirements)
Mechanical:	10 lbs/6 oz. 3.6Hx15.7Wx12.8D Convection cooled	Reduced size and appearance, to spec.
Display:	4 line x 20 backlit LCD	4 x 40 LCD
Video:	Integrated XGA 1280 x 1024	Still or full motion, MPEG 2, NTSC/PAL, via PCI slot
Digital Audio:	2 Stereo channels 1V RMS max. level 20 bit, 20-20k Freq. Response S/N >90 dB, S/N +D. 85 dB Compression: MS Audio / MP-3 16,22.05,24,32,44.1,48 kHz S.R.	8, 10, 12 channels, ADPCM, CELP, MPEG 2, via PCI or ISA slot.
Input/Outputs:	Front panel nav. buttons (8) Infrared remote trans/receiver Rear panel RCA audio jacks (6) (2) RJ-6 phone line in and pass thru. RJ-45 LAN connection.	Supports up to (13) navigation buttons. Rear panel connections can be customized.